



SUPER SPEC[®] ALKYD CALCIMINE RECOATER 306

Features

- Features a uniform, glare-free finish.
- Provides a highly serviceable film.
- Superior leveling and hiding qualities.
- Superb problem-solver coating that excels over difficult recoat surfaces.
- No need for primer over calcimine coatings

General Description

A premium quality, high hiding, alkyd flat paint specifically designed for recoating surfaces previously painted with calcimine material. Covers most wall, ceiling, and trim surfaces in one coat.

Recommended For

Residential or commercial applications where a premium quality finish is desired. Specifically formulated for recoating surfaces previously painted with calcimine material.

Limitations

- Do not apply when air and surface temperatures are below 50° F (10° C).
- Not available in all areas.

Product Information

<p>Colors: —Standard: White (White may be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview[®] colorants per gallon.)</p>	<table border="1"> <thead> <tr> <th>Technical Data[∅]</th> <th>Paste Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>48%</td> </tr> </tbody> </table>	Technical Data [∅]	Paste Base	Vehicle Type	Alkyd	Pigment Type	Titanium Dioxide	Volume Solids	48%						
Technical Data [∅]	Paste Base														
Vehicle Type	Alkyd														
Pigment Type	Titanium Dioxide														
Volume Solids	48%														
<p>—Tint Bases: Benjamin Moore & Co. Color Preview[®] bases 1B & 2B</p>	<table border="1"> <tbody> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>400 – 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet 3.8 mils – Dry 1.8 mils</td> </tr> </tbody> </table>	Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.	Recommended Film Thickness	– Wet 3.8 mils – Dry 1.8 mils										
Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.														
Recommended Film Thickness	– Wet 3.8 mils – Dry 1.8 mils														
<p>—Special Colors: Contact your Benjamin Moore & Co., representative</p>	<p>Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</p> <table border="1"> <tbody> <tr> <td>Dry Time @ 77° F</td> <td>– To Touch</td> <td>4 – 6 Hours</td> </tr> <tr> <td>(25° C) @ 50% RH</td> <td>– To Recoat</td> <td>12 Hour</td> </tr> </tbody> </table>	Dry Time @ 77° F	– To Touch	4 – 6 Hours	(25° C) @ 50% RH	– To Recoat	12 Hour								
Dry Time @ 77° F	– To Touch	4 – 6 Hours													
(25° C) @ 50% RH	– To Recoat	12 Hour													
<p>Certification: VOC compliant in federally regulated areas only Master Painters Institute MPI #49</p>	<p>Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.</p> <table border="1"> <tbody> <tr> <td>Dries By</td> <td>Oxidations</td> </tr> <tr> <td>Viscosity</td> <td>103 ± 3 KU</td> </tr> <tr> <td>Flash Point</td> <td>Combustible</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Flat</td> </tr> </tbody> </table>	Dries By	Oxidations	Viscosity	103 ± 3 KU	Flash Point	Combustible	Gloss / Sheen	Flat						
Dries By	Oxidations														
Viscosity	103 ± 3 KU														
Flash Point	Combustible														
Gloss / Sheen	Flat														
<p>Technical Assistance: Available through your local authorized Benjamin Moore[®] retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages</p>	<table border="1"> <tbody> <tr> <td>Surface Temperature at Application</td> <td>– Min. 50° F – Max. 90° F</td> </tr> <tr> <td>Thin With</td> <td>Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Mineral Spirits</td> </tr> <tr> <td>Weight Per Gallon</td> <td>13.3 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 40° F – Max. 90° F</td> </tr> <tr> <td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td>397 Grams/Liter</td> <td>3.32 lbs./Gallon</td> </tr> </tbody> </table>	Surface Temperature at Application	– Min. 50° F – Max. 90° F	Thin With	Do Not Thin	Clean Up Thinner	Mineral Spirits	Weight Per Gallon	13.3 lbs	Storage Temperature	– Min. 40° F – Max. 90° F	Volatile Organic Compounds (VOC)		397 Grams/Liter	3.32 lbs./Gallon
Surface Temperature at Application	– Min. 50° F – Max. 90° F														
Thin With	Do Not Thin														
Clean Up Thinner	Mineral Spirits														
Weight Per Gallon	13.3 lbs														
Storage Temperature	– Min. 40° F – Max. 90° F														
Volatile Organic Compounds (VOC)															
397 Grams/Liter	3.32 lbs./Gallon														

[∅]Reported values are for Pastel Bases. Contact Benjamin Moore & Co for values of other bases or colors

Surface Preparation

Surfaces to be painted must be clean and free of dirt, wax, soap, oil, grease, and water soluble materials. Glossy areas should be dulled.

Difficult Substrates: Benjamin Moore® offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

Note: All alkyd-based enamels experience a certain amount of yellowing. This effect is accelerated in dark or poorly ventilated areas.

This product is sold only for the repainting of surfaces previously painted with calcimine material. For new surfaces or surfaces previously painted with non-calcimine coatings, a variety of Benjamin Moore® interior products are available. Consult your Benjamin Moore® retailer for recommendations.

Application

Mixing of Paint: Stir thoroughly before and occasionally during use. Apply with a quality china bristle brush, or all purpose synthetic brush, short nap roller, or airless spray.

Do not apply when air and surface temperatures are below 50° F (10° C).

Spray, Airless: Fluid Pressure — 1,500 to 2,000 PSI;
Tip: .013 - .017 Orifice

Thinning/Cleaning

Do not thin. Clean up with mineral spirits.

USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Save unused product for touch-up purposes or a household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for more information on disposal options.**

Environmental, Health & Safety Information

WARNING! COMBUSTIBLE LIQUID AND VAPOR

Contains Stoddard Solvent and Crystalline Silica

VAPOR HARMFUL. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION

NOTICE: Repeated and prolonged exposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Crystalline Silica** can cause cancer when in the respirable form (spray mist or sanding dust).

Keep away from heat and flame. **Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. To avoid breathing vapors or spray mist, open window and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear a properly fitted vapor/particulate respirator approved by NIOSH for use with paints or leave the area. In all cases follow respirator manufacturer's directions for respirator use. Close container after each use.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion - DO NOT INDUCE VOMITING, get medical help immediately.

IN CASE OF: FIRE – Use foam, CO2, dry chemical, or water fog.
SPILL – Absorb with inert material and dispose of as specified under **Thinning/Cleanup**.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for
additional health and safety information.**