



SUPER HIDE[®]

ZERO VOC INTERIOR

SEMI-GLOSS 358

Features

- Good hide
- Great touch up
- Spatter resistant
- Qualifies for LEED[®] credit
- Quick dry
- Low odor
- Easy application
- Qualifies for LEED[®] V4 Low Emitting Products credit

Recommended For

Interior wall and ceiling surfaces in commercial and institutional environments where a semi-gloss finish is desired. For new or previously painted interior wallboard, masonry, and primed or previously painted plaster, wood or metal.

General Description

A professional-quality interior waterborne semi-gloss finish tinted with Benjamin Moore's proprietary zero VOC colorants. This waterborne interior semi-gloss qualifies for LEED[®] credit and is MPI approved.

Limitations

- Do not apply when air and surface temperatures are below 50°F (10°C).

Product Information

Colors — Standard:

01 White, 03 Bone White, 70 Linen White, 73 Navajo White, 74 China White

— Tint Bases:

Bases: 1X, 2X & 3X

Tint bases **only** with Benjamin Moore[®] Gennex[®] Waterborne colorant.

— Special Colors:

Contact your Benjamin Moore[®] representative.

Certification:

VOC compliant in all regulated areas.

Zero VOC according to EPA Method 24

Qualifies for LEED[®] V4 low emission credit under Environmental Air Quality-Low-Emitting Products based on representative sample testing at an accredited independent third party lab.

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

Master Painters Institute MPI #43 and 43 X-Green.

LEED [®] Latex Non-Flat LEED [®] for Schools	CHPS (Collaborative for High Performance Schools)	VOC (any color)
YES	YES	0 g/l

Technical Assistance:

Available through your local authorized independent Benjamin Moore[®] retailer. For the location of the retailer nearest you, 1-800-826-2623, see www.benjaminmoore.com or consult your local Yellow Pages.

Technical Data[◇]

White

Vehicle Type	Acrylic
Pigment Type	Titanium Dioxide
Volume Solids	32.7 ± 2%
Coverage per Gallon at Recommended Film Thickness	400 – 450 sq. ft. (37.2 – 41.8 sq. m.)
Recommended Film Thickness	– Wet 3.8 mils – Dry 1.2 mils
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Dry Time @ 77°F (25°C) @ 50% RH	– To Touch 2 Hours – To Recoat 4 Hours
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.	
Dries By	Coalescence
Viscosity	104 ± 3KU
Flash Point	N/A
Gloss / Sheen	Semi-gloss (20-35 @ 60°)
Surface Temperature at Application	– Min. 50°F (10°C) – Max. 90°F (32°C)
Thin With	See Chart
Clean Up Thinner	Clean Water
Weight Per Gallon	10.1 lbs (4.8 Kg)
Storage Temperature	– Min. 40°F (4°C) – Max. 90°F (32°C)

Volatile Organic Compounds (VOC)

0 Grams/Liter 0 Lbs./Gallon

Zero VOC post tint (any base and any color)

[◇]Reported values are for White. Contact Benjamin Moore[®] for values of other bases or colors.

Super Hide® Zero VOC Interior Semi-Gloss 358

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure 30 days before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry.

Difficult Substrates: Benjamin Moore® offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant color change is desired. Consult your retailer or a Benjamin Moore® representative.

Wood, and Engineered Wood Products:

Primer: Super Hide® Zero VOC Interior Primer (354) or Ultra Spec® 500 Interior Latex Primer (N534).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Bleeding Type Woods, (Redwood and Cedar):

Primer: Fresh Start® Multi-Purpose Oil Based Primer (N024)

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Drywall:

Primer: Super Hide® Zero VOC Interior Primer (354) or Ultra Spec® 500 Interior Latex Primer (N534).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Plaster:

Primer: Fresh Start® Multi-Purpose Latex Primer (N023) or Fresh Start® High-Hiding All Purpose Primer (046).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Rough or Pitted Masonry:

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (571).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Smooth Poured or Precast Concrete:

Primer: Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (608) or Fresh Start® Multi-Purpose Latex Primer (N023).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Ferrous Metal (Steel and Iron):

Primer: Ultra Spec HP® Acrylic Metal Primer (HP04) or Super Spec HP® Alkyd Metal Primer (P06).

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Non-Ferrous Metal (Galvanized & Aluminum):

All new metal surfaces must be thoroughly cleaned with Corotect® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

Primer: Ultra Spec HP® Acrylic Metal Primer (HP04)

Finish: 1 or 2 coats Super Hide® Zero VOC Interior Semi-Gloss (358)

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir thoroughly before use. Apply one or two coats. For best results, use a Benjamin Moore® Professional custom-blended nylon/polyester brush, Benjamin Moore® Professional roller, or a similar product. This product can also be sprayed.

Conditioning with Benjamin Moore® 518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance

	Mild Conditions	Severe Conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
Brush: Nylon / Polyester	No thinning necessary	Add 518 Extender or water: Max of 8 fl. oz. to a gallon of paint Never add other paints or solvents.
Roller: Premium Quality 3/8" roller cover		
Spray: Airless Pressure: 2000 -2800 psi Tip: 0.011-0.015		

Clean Up

Clean Up: Use soap and water. Spray equipment should be given a final rinse with mineral spirits to prevent corrosion. Follow state/local guidelines on solvent use.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information.**