

SAFETY DATA SHEET

Revision Date: 22-Sep-2015

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Product Class Color Recommended use Restrictions on use

REGAL SELECT WATERBORNE INTERIOR FLAT FINISH LINEN WHITE 54770 WATER THINNED PAINT White

Manufacturer Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 855-724-6802

www.benjaminmoore.com

Emergency Telephone Number(s) CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

Paint

No information available

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not Applicable

Other information No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Titanium dioxide	13463-67-7	20
Kaolin, calcined	92704-41-1	10
Limestone	1317-65-3	10
Diatomaceous earth	61790-53-2	5
Silica, amorphous	7631-86-9	5
Nepheline syenite	37244-96-5	5

	4. FIRST A	ID MEASURES	
General Advice	No hazards which require special first aid measures.		
Eye Contact	Rinse thoroughly with physician.	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.		
Inhalation	Move to fresh air. If s	ymptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.		
Most Important Symptoms/Effects	None known.		
Notes To Physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			
	5. FIRE-FIGH	TING MEASURES	
Suitable Extinguishing Media	5. FIRE-FIGH	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Suitable Extinguishing Media Protective Equipment And Pred Firefighters		Use extinguishing measures that are appropriate to local	
Protective Equipment And Pred	cautions For	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)	
Protective Equipment And Pred Firefighters	cautions For The Chemical	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or	
Protective Equipment And Pred Firefighters Specific Hazards Arising From	cautions For The Chemical Ict	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or extreme heat.	

Flammability: 0

Flammability Limits In Air

Lower Explosion Limit Upper Explosion Limit

Health: 1

Not applicable Not applicable

Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High

NFPA

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Instability: 0

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental Precautions	See Section 12 for additional Ecological Information.
Methods For Clean-Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	OSHA
Titanium dioxide	10 mg/m ³ - TWA	15 mg/m³ - TWA
Limestone	N/E	15 mg/m³ - TWA total 5 mg/m³ - TWA
Diatomaceous earth	N/E	- (80)/(% SiO2) mg/m³ TWA 20 mppcf - TWA
Silica, amorphous	N/E	- (80)/(% SiO2) mg/m³ TWA 20 mppcf - TWA
Nepheline syenite	N/E	5 mg/m ³ - TWA (nuisance dust)

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.		
Personal Protective Equipment			
Eye/Face Protection	Safety glasses with side-shields.		
Skin Protection	Protective gloves and impervious clothing.		
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.		
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** рĤ Viscosity (cps) Solubility Water Solubility **Evaporation Rate** Vapor Pressure Vapor Density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) **Flash Point Method** Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F) **Decomposition Temperature (°C)** Partition Coefficient (n-octanol/water)

liquid little or no odor No information available 11.2 - 11.3 1.34 - 1.36 No information available 50 - 60 35 - 45 40 - 50 55 - 65 0 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions To Avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of exposure		
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Information on toxicological ef	fects	
Symptoms	No information available	
Delayed and immediate effects	as well as chronic effects from short and long-term exposure	
Eye contact Skin contact	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.	
Inhalation Ingestion	May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Sensitization: Neurological Effects Mutagenic Effects	No information available No information available. No information available.	
Reproductive Effects Developmental Effects	No information available. No information available.	
Target Organ Effects STOT - single exposure	No information available. No information available.	
STOT - repeated exposure Other adverse effects Aspiration Hazard	No information available. No information available. No information available	
Numerical measures of toxicity		
The following values are calculated based on chapter 3.1 of the GHS document		
ATEmix (oral) ATEmix (dermal)	17692 mg/kg 93014 mg/kg	
O		

<u>Component</u>

Acute Toxicity

Titanium dioxideLD50 Oral: > 10000 mg/kg (Rat)LD50 Dermal: > 10000 mg/m³ (Rabbit)LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)Kaolin, calcinedLD50 Oral: > 5000 mg/kg (Rat) vendor dataLimestoneLD50 Oral: 6,450 mg/kg (Rat) vendor dataSilica, amorphousLD50 Oral: > 5000 mg/kg (Rat)LD50 Oral: > 5000 mg/kg (Rat)LD50 Oral: > 2 mg/L

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS	
Waste Disposal Method	Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.	
	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	
	15. REGULATORY INFORMATION	
International Inventories		
TSCA: United States DSL: Canada	Yes - All components are listed or exempt. Yes - All components are listed or exempt.	
Federal Regulations		
SARA 311/312 hazardous categorizationAcute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo		

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	Х	X	X
Limestone	X	X	X
Diatomaceous earth		X	
Silica, amorphous	Х	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS	Health: 1	Flammability: 0	Reactivity: 0	PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 855-724-6802
Revision Date:	22-Sep-2015
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET