



Revision Date: 06-Feb-2017 Revision Number: 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ACRYLIC METAL PRIMER GRAY

Product Code V110-72FR

Alternate Product Code A11072

Product Class WATER THINNED PAINT

**Color** Gray

Recommended use Industrial paint

Restrictions on use No information available

#### **Manufactured For**

Benjamin Moore & Co., Limited 8775 Keele Street

Concord ON L4K 2N1 Phone: 1-800-361-5898 corotechcoatings.ca

### Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 800-225-5554 corotechcoatings.com

**Emergency Telephone Number(s)** 

CANUTEC: 613-996-6666

## 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

## Label elements

### Danger

#### Hazard statements

May cause cancer

Causes damage to organs through prolonged or repeated exposure



Appearance liquid Odor little or no odor

### **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Do not breathe dust/fume/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

### **Precautionary Statements - Response**

If exposed or concerned get medical attention

#### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Silica, crystalline	14808-60-7	10 - 30%
Titanium dioxide	13463-67-7	5 - 10%
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	1 - 5%
Diethylene glycol monoethyl ether	111-90-0	1 - 5%
Zinc phosphate	7779-90-0	1 - 5%
Wollastonite	13983-17-0	1 - 5%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Aluminum oxide	1344-28-1	0.1 - 0.25%

# 4. FIRST AID MEASURES

**General Advice** 

No hazards which require special first aid measures.

**Eye Contact** 

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

V110-72FR - ACRYLIC METAL PRIMER GRAY

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 06-Feb-2017

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective Equipment And Precautions For** 

**Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

**Flash Point Data** 

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

#### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

V110-72FR - ACRYLIC METAL PRIMER GRAY

Other Information Prevent further leakage or spillage if safe to do so.

**Environmental Precautions**See Section 12 for additional Ecological Information.

Methods For Clean-Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 06-Feb-2017

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure Limits**

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Silica, crystalline	0.025 mg/m <sup>3</sup> - TWA	0.025 mg/m <sup>3</sup> - TWA	0.025 mg/m <sup>3</sup> - TWA	0.10 mg/m <sup>3</sup> - TWA	0.1 mg/m <sup>3</sup> - TWAEV
Titanium dioxide	10 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV
Diethylene glycol monoethyl ether	N/E	N/E	N/E	30 ppm - TWA 165 mg/m³ - TWA	N/E
Wollastonite	N/E	N/E	N/E	N/E	10 mg/m³ - TWAEV 5 mg/m³ - TWAEV
Ethanol, 2-(2-butoxyethoxy)-	10 ppm - TWA	N/E	N/E	10 ppm - TWA	N/E
Zinc oxide	2 mg/m³ - TWA 10 mg/m³ - STEL	10 mg/m³ - TWAEV 5 mg/m³ - TWAEV 10 mg/m³ - STEV			
Aluminum oxide	1 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	1.0 mg/m <sup>3</sup> - TWA	1 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

Eye/Face Protection
Skin Protection

**Respiratory Protection** 

Safety glasses with side-shields.

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

**Hygiene Measures** 

Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

liquid **Appearance** 

little or no odor Odor

**Odor Threshold** No information available

Density (lbs/gal) 10.5 - 10.6 **Specific Gravity** 1.26 - 1.28

No information available На Viscosity (cps) No information available

Solubility No information available **Water Solubility** No information available **Evaporation Rate** No information available **Vapor Pressure** No information available **Vapor Density** No information available

Wt. % Solids 50 - 60 35 - 45 Vol. % Solids Wt. % Volatiles 40 - 50 Vol. % Volatiles 55 - 65 **VOC Regulatory Limit (g/L)** < 250 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing Point (°F) 32

Freezing Point (°C) Flash Point (°F) Not applicable Flash Point (°C) Not applicable **Flash Point Method** Not applicable Not applicable Flammability (solid, gas) Not applicable **Upper Explosion Limit** Not applicable **Lower Explosion Limit** 

No information available **Autoignition Temperature (°F) Autoignition Temperature (°C)** No information available **Decomposition Temperature (°F)** No information available **Decomposition Temperature (°C)** No information available Partition Coefficient (n-octanol/water) No information available

### 10. STABILITY AND REACTIVITY

O

Reactivity Not Applicable

Stable under normal conditions. **Chemical Stability** 

Prevent from freezing. **Conditions To Avoid** 

No materials to be especially mentioned. **Incompatible Materials** 

**Hazardous Decomposition Products** None under normal use.

**Possibility Of Hazardous Reactions** None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

**Product Information** 

V110-72FR - ACRYLIC METAL PRIMER GRAY

### Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Ingestion

Product Information No information available

Information on toxicological effects

Symptoms No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 06-Feb-2017

**Inhalation** May cause irritation of respiratory tract.

Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization:No information available.Neurological EffectsNo information available.Mutagenic EffectsNo information available.Reproductive EffectsNo information available.Developmental EffectsNo information available.Target Organ EffectsNo information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organ

Causes damage to organs through prolonged or repeated exposure if inhaled. Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or

dust from sanding the dried paint.

Other adverse effects
Aspiration Hazard
No information available.
No information available.

#### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2976 mg/kg
ATEmix (dermal) 126476 mg/kg
ATEmix (inhalation-dust/mist) 167.4 mg/L

#### Component

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat)

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)
Diethylene glycol monoethyl ether
LD50 Oral: 7,500 mg/kg (Rat)
LD50 Dermal: 4200 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 5240 mg/m<sup>3</sup> (Rat)

Ethanol, 2-(2-butoxyethoxy)-LD50 Oral: 3384 mg/kg (Rat)

LD50 Dermal: 2700 mg/kg (Rabbit)

Zinc oxide

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)

## **Chronic Toxicity**

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	
	1 - Human Carcinogen	Known Human Carcinogen	
Silica, crystalline		-	
	2B - Possible Human Carcinogen		
Titanium dioxide			
Aluminum oxide		Reasonably Anticipated Human Carcinogen	

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is

#### Leaend

IARC - International Agency for Research on Cancer

bound to other materials, such as paint."

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

### **Bioaccumulation / Accumulation**

No information available.

#### **Mobility in Environmental Media**

No information available.

# Ozone

No information available

### Component

### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

## **Acute Toxicity to Aquatic Invertebrates**

Ethanol, 2-(2-butoxyethoxy)-EC50: 100 mg/L (Daphnia - 48 hr.)

## **Acute Toxicity to Aquatic Plants**

No information available

## 13. DISPOSAL CONSIDERATIONS

### **Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 06-Feb-2017

## 14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.

Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical NameCAS-NoWeight % (max)NPRI Parts 1- 4Propanoic acid, 2-methyl-, monoester25265-77-41 - 5%Listed

with 2,2,4-trimethyl-1,3-pentanediol			
Diethylene glycol monoethyl ether	111-90-0	1 - 5%	Listed
Zinc phosphate	7779-90-0	1 - 5%	Listed
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5%	Listed
Zinc oxide	1314-13-2	1 - 5%	Listed
Aluminum oxide	1344-28-1	0.1 - 0.25%	Listed

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

Chemical Name	CAS-No	Weight % (max)	NPRI Part 5
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5%	Listed

### **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

## 16. OTHER INFORMATION

HMIS\_- Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

## **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked guestions-guestions posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

855-724-6802

**Revision Date:** 06-Feb-2017 **Reason For Revision** Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**